

SAP Note



1135105 - Printer Vendor Wizard Note: Toshiba TEC

**Version** 39    **Validity:**  
03.07.2018 - active

**Language** English (Master)

## Header Data

<b>Release Status</b>	For Checking (Target Status: Released for Customer)
<b>Component</b>	BC-CCM-PRN-PVP-TT SAP Printer Vendor program: Toshiba TEC <a href="#">Display ACRF Content</a>
<b>Other Components</b>	<a href="#">BC-CCM-PRN-DVM Printer Administration</a>
<b>Priority</b>	Recommendations / Additional Info
<b>Responsible</b>	Chikahiro Saegusa ( C5184583 )
<b>Processor</b>	Parvathy S ( I061455 )
<b>Category</b>	Special development
<b>Relevant for Translation</b>	Yes

## Symptom

The company Toshiba TEC is member of the SAP Printer Vendor program and offers within this program support for the printer model / device type pairs listed below.

For general information about the SAP Printer Vendor program please check note 1130927.

The printer model / device type combinations are visible in the newest data version of the "device type wizard". Please read note 1036961 for a description how to use the device type wizard and how to select one of the combinations shown below.

The device types are delivered as attachments to this note. Please download the files and proceed with the installation as described in note 1103422.

Certain features of the device types become active only with the following releases and support package levels:

Additional print options: (see note 1049778)

SAP\_BASIS 6.20 SP63 and higher

SAP\_BASIS 6.40 SP21 and higher

SAP\_BASIS 7.00 SP14 and higher

SAP\_BASIS 7.10 standard

## Other Terms

SPAD , device type , SAP Printer Vendor program

## Reason and Prerequisites

[Enter your Reason and Prerequisites here...]

## Solution

Supported Printer model/ device type combinations:

ID	Printer model	device type	character set	version
[001]	/ e-STUDIO6530C Series	/ TT6CI11.PRI	/ ISO1	/ 1.1
[002]	/ e-STUDIO4520C Series	/ TT4EI11.PRI	/ ISO1	/ 1.1
[003]	/ e-STUDIO455 Series	/ TT4PI11.PRI	/ ISO1	/ 1.1
[004]	/ e-STUDIO855 Series	/ TT8NI11.PRI	/ ISO1	/ 1.1
[005]	/ e-STUDIO6530C Series	/ TT6CI21.PRI	/ ISO2	/ 1.1
[006]	/ e-STUDIO4520C Series	/ TT4EI21.PRI	/ ISO2	/ 1.1
[007]	/ e-STUDIO455 Series	/ TT4PI21.PRI	/ ISO2	/ 1.1
[008]	/ e-STUDIO855 Series	/ TT8NI21.PRI	/ ISO2	/ 1.1
[009]	/ e-STUDIO262CP 263CS	/ TTC2I11.PRI	/ ISO1	/ 1
[010]	/ e-STUDIO382P 332P	/ TTM3I11.PRI	/ ISO1	/ 1
[011]	/ e-STUDIO223CS 222CS 222CP	/ TTD2I11.PRI	/ ISO1	/ 1
[012]	/ e-STUDIO6550C Series	/ TT6DI11.PRI	/ ISO1	/ 1
[013]	/ e-STUDIO4540C Series	/ TT4FI11.PRI	/ ISO1	/ 1
[014]	/ e-STUDIO6550C Series	/ TT6DI21.PRI	/ ISO2	/ 1
[015]	/ e-STUDIO4540C Series	/ TT4FI21.PRI	/ ISO2	/ 1
[016]	/ e-STUDIO263CS	/ TTD2JA1.PRI	/ JAPANESE	/ 1
[017]	/ e-STUDIO456 Series	/ TT4QI11.PRI	/ ISO1	/ 1
[018]	/ e-STUDIO856 Series	/ TT8OI11.PRI	/ ISO1	/ 1
[019]	/ e-STUDIO456 Series	/ TT4QI21.PRI	/ ISO2	/ 1
[020]	/ e-STUDIO856 Series	/ TT8OI21.PRI	/ ISO2	/ 1
[021]	/ e-STUDIO332S	/ TTN3I11.PRI	/ ISO1,2,5,7,9	/ 1
[022]	/ e-STUDIO403S	/ TTM4I11.PRI	/ ISO1,2,5,7,9	/ 1
[023]	/ e-STUDIO2550C Series	/ TT2CI11.PRI	/ ISO1	/ 1
[024]	/ e-STUDIO2550C Series	/ TT2CI21.PRI	/ ISO2	/ 1
[025]	/ e-STUDIO224CS	/ TTE2U81.PRI	/ ISO1,2,5,7,9	/ 1
[026]	/ e-STUDIO263CP 264CS	/ TTF2U81.PRI	/ ISO1,2,5,7,9	/ 1
[027]	/ e-STUDIO383P	/ TTO3U81.PRI	/ ISO1,2,5,7,9	/ 1
[028]	/ e-STUDIO306LP Series	/ TT3MI11.PRI	/ ISO1	/ 1
[029]	/ e-STUDIO306LP Series	/ TT3MI21.PRI	/ ISO2	/ 1
[030]	/ e-STUDIO407CS Series	/ TT4GI11.PRI	/ ISO1	/ 1
[031]	/ e-STUDIO407CS Series	/ TT4GI21.PRI	/ ISO2	/ 1
[032]	/ e-STUDIO527S Series	/ TT5MI11.PRI	/ ISO1	/ 1
[033]	/ e-STUDIO527S Series	/ TT5MI21.PRI	/ ISO2	/ 1
[034]	/ e-STUDIO307LP Series	/ TT3MI11.PRI	/ ISO1	/ 1
[035]	/ e-STUDIO307LP Series	/ TT3MI21.PRI	/ ISO2	/ 1
[036]	/ e-STUDIO385S	/ TTP3I11.PRI	/ ISO1	/ 1
[037]	/ e-STUDIO385P	/ TTQ3I11.PRI	/ ISO1	/ 1
[038]	/ e-STUDIO305CS	/ TTC3I11.PRI	/ ISO1	/ 1
[039]	/ e-STUDIO305CP	/ TTD3I11.PRI	/ ISO1	/ 1
[040]	/ e-STUDIO525P	/ TTM5I11.PRI	/ ISO1	/ 1
[041]	/ e-STUDIO306CS	/ TTE3I11.PRI	/ ISO1	/ 1
[042]	/ e-STUDIO425S	/ TTN4I11.PRI	/ ISO1	/ 1
[043]	/ e-STUDIO5005AC Series	/ TT5CI11.PRI	/ ISO1+UPE	/ 1
[044]	/ e-STUDIO5005AC Series	/ TT5CI21.PRI	/ ISO2	/ 1
[045]	/ e-STUDIO5008A Series	/ TT5NI11.PRI	/ ISO1+UPE	/ 1
[046]	/ e-STUDIO5008A Series	/ TT5NI21.PRI	/ ISO2	/ 1
[047]	/ e-STUDIO7506AC Series	/ TT7CI11.PRI	/ ISO1+UPE	/ 1
[048]	/ e-STUDIO7506AC Series	/ TT7CI21.PRI	/ ISO2	/ 1

[049] / e-STUDIO8508A Series / TT8PI11.PRI / ISO1+UPE / 1  
 [050] / e-STUDIO8508A Series / TT8PI21.PRI / ISO2 / 1  
 [051] / e-STUDIO5008LP\_Loops-LP50 Series / TT5OI11.PRI / ISO1+UPE / 1  
 [052] / e-STUDIO5008LP\_Loops-LP50 Series / TT5OI21.PRI / ISO2 / 1  
 [053] / e-STUDIO408S / TTO4I11.PRI / ISO1 / 1  
 [054] / e-STUDIO448S / TTP4I11.PRI / ISO1 / 1  
 [055] / e-STUDIO478S / TTQ4I11.PRI / ISO1 / 1  
 [056] / e-STUDIO408P / TTR4I11.PRI / ISO1 / 1  
 [057] / e-STUDIO478P / TTS4I11.PRI / ISO1 / 1

- \* e-STUDIO6530C Series: e-STUDIO5520C/6520C/6530C
- \* e-STUDIO4520C Series: e-STUDIO2020C/2330C/2820C/2830C/  
3520C/3530C/4520C/3520Ci
- \* e-STUDIO455 Series: e-STUDIO205L/255/305/355/455/  
305S/355S/455S/305SD/355SD/455SD
- \* e-STUDIO855 Sreies: e-STUDIO555/655/755/855
- \* e-STUDIO6550C Series: e-STUDIO5540C/6540C/6550C/5560C/6560C/6570C
- \* e-STUDIO4540C Series: e-STUDIO2040C/2540C/3040C/3540C/4540C
- \* e-STUDIO456 Series: e-STUDIO206L/256/306/356/456/207L/257/307/357/457/507
- \* e-STUDIO856 Sreies: e-STUDIO556/656/756/856/557/657/757/857
- \* e-STUDIO2550C Series: e-STUDIO2050C/2550C/  
2555C/3055C/3555C/4555C/5055C
- \* e-STUDIO306LP Series: Loops-LP30/e-STUDIO306LP
- \* e-STUDIO407CS Series: e-STUDIO287CS/347CS/407CS
- \* e-STUDIO527S Series: e-STUDIO527S/477S
- \* e-STUDIO307LP Series: Loops-LP301/e-STUDIO307LP
- \* e-STUDIO5005AC Series: e-STUDIO2000AC/2500AC/2005AC/2505AC/3005AC/3505AC/4505AC/5005AC
- \* e-STUDIO5008A Series: e-STUDIO2008A/2508A/3008A/3508A/4508A/5008A
- \* e-STUDIO7506AC Series: e-STUDIO5506AC/6506AC/7506AC
- \* e-STUDIO8508A Series: e-STUDIO5508A/6508A/7508A/8508A
- \* e-STUDIO5008LP\_Loops-LP50 Series: e-STUDIO3508LP\_Loops-LP35/4508LP\_Loops-LP45/5008LP\_Loops-LP50
- \* ISO1: Latin 1, ISO2: Latin 2.
- \* ISO5: Cyrillic, ISO7: Greek, ISO9: Turkey.
- \* UPE: Unicode Print Enable

#### Note: Hold Print

To use the "Hold Print" function in e-STUDIO5520C/6520C/6530C, the system ROM version should be T430SY0\*200 or later.

To use the "Hold Print" function in e-STUDIO2020C/2330C/2820C/2830C/3520C/3530C/4520C/3520Ci, the system ROM version should be T450SY0\*201 or later.

The device type files [001] TT6CI11.PRI, [002] TT4EI11.PRI, [005] TT6CI21.PRI, [006] TT4EI21.PRI do not contain an entry for "Hold Print". If you want to use the "Hold Print" function, please follow the instructions below:

- In "Printer Initialization" screen, find a line @PJL COMMENT DSSC PRINT  
PRINTMODE=NORMAL and change the value from "NORMAL" to "HOLD".

#### Label Printers

The device types listed below can be used to convert a label created using Smart Forms into the ZPL II printer control language and to print it on the Z-Mode enabled Toshiba TEC label printers. In this case, the label is designed in Smart Forms and not by an external program for designing labels. (See SAP Note 168368 for Smart Forms).

ID	Printer model	Device type	Character set	Driver
[L001]	/ B-EX 203dpi	/ TTLZBI12.PRI	/ ISO1	/ LZPL
[L002]	/ B-EX 300dpi	/ TTLZBI13.PRI	/ ISO1	/ LZPL
[L003]	/ B-EX 600dpi	/ TTLZBI16.PRI	/ ISO1	/ LZPL
[L004]	/ B-SA 203dpi.....	/ TTLZBI12.PRI.....	/ ISO1.....	/ LZPL
[L005]	/ B-SA 300dpi.....	/ TTLZBI13.PRI.....	/ ISO1.....	/ LZPL
[L006]	/ B-SX6T.....	/ TTLZBI13.PRI.....	/ ISO1.....	/ LZPL

\* B-EX 203dpi: B-EX4T2-G, B-EX4T1-G, B-EX4D2-G

\* B-EX 300dpi: B-EX4T2-T, B-EX4T1-T, B-EX4D2-T

\* B-EX 600dpi: B-EX4T2-H

\* B-SA 203dpi: B-SA4TM-G, B-SA4TP-G

\* B-SA 300dpi: B-SA4TM-T, B-SA4TP-T

\* B-EX4T2 print heads are Flat-type with Paper aligned to Left and B-EX4T1 print heads are Near-edge with Paper aligned to the Center.

#### Note:

- 1) To use LZPL driver, read SAP Note [750772](#) for release level requirements and restrictions.
- 2) When printing a Smart Form, user is advised to examine the actual printout of the form from the printer, rather than just relying on the print preview image.
- 3) Following cases may occur while printing Smart Forms:
  - a) Print position and font size are slightly different.
  - b) Toshiba TEC's printer specifications apply, for example the memory capacity and the number of fields.
  - c) If an object is placed outside the print area or the print start position of an object is placed within the print area but the end position is outside the print area, the part beyond the print area will be printed starting on the left end of the new line.

#### Label Printers (Device Types and ABAP based printer driver supporting TPCL)

The device types listed below can be used to convert a label created using Smart Forms into the Toshiba printer control language and to print it on the Toshiba TEC label printers. In this case, the label is designed in Smart Forms and not by an external program for designing labels. (See SAP Note 168368 for Smart Forms).

For receiving the device types and ABAP driver files, please contact by e-mail to TEC-barcode-support-MLGrp@ml.toshiba.co.jp

Following are device types supporting ISO 8859-1(LATIN-1) character set.

ID	Printer model	Device type
[LLA101]	/ B-EX4T1-G(LN)	/ YTLLNX0G.PRI
[LLA102]	/ B-EX4T2-G(LN)	/ YTLLNX0G.PRI
[LLA103]	/ B-EX4D2-G(LN)	/ YTLLNX0G.PRI
[LLA104]	/ B-EX4T1-T(LN)	/ YTLLNX0T.PRI
[LLA105]	/ B-EX4T2-T(LN)	/ YTLLNX1T.PRI
[LLA106]	/ B-EX4T2-H(LN)	/ YTLLNX1H.PRI
[LLA107]	/ B-EX4T3-H(LN)	/ YTLLNX3H.PRI
[LLA108]	/ B-EX6T1-G(LN)	/ YTLLNX4G.PRI
[LLA109]	/ B-EX6T3-G(LN)	/ YTLLNX4G.PRI
[LLA110]	/ B-EX6T1-T(LN)	/ YTLLNX4T.PRI
[LLA111]	/ B-EX6T3-T(LN)	/ YTLLNX4T.PRI
[LLA112]	/ B-SX4T(LN)	/ YTLLNH0G.PRI
[LLA113]	/ B-SX5T(LN)	/ YTLLNH1T.PRI
[LLA114]	/ B-SX8T(LN)	/ YTLLNH2T.PRI
[LLA115]	/ B-SA4TP-G(LN)	/ YTLLNA0G.PRI
[LLA116]	/ B-SA4TM-G(LN)	/ YTLLNA0G.PRI
[LLA117]	/ B-SA4TP-T(LN)	/ YTLLNA0T.PRI
[LLA118]	/ B-SA4TM-T(LN)	/ YTLLNA0T.PRI
[LLA119]	/ B-FV4D-G(LN)	/ YTLLNV0G.PRI
[LLA120]	/ B-FV4T-G(LN)	/ YTLLNV0G.PRI

[LLA121] / B-EV4D-G(LN) / YTLLNV0G.PRI  
[LLA122] / B-EV4T-G(LN) / YTLLNV0G.PRI  
[LLA123] / B-FV4D-T(LN) / YTLLNV0T.PRI  
[LLA124] / B-FV4T-T(LN) / YTLLNV0T.PRI  
[LLA125] / B-EV4D-T(LN) / YTLLNV0T.PRI  
[LLA126] / B-EV4T-T(LN) / YTLLNV0T.PRI  
[LLA127] / B-EP2D(LN) / YTLLNP1G.PRI  
[LLA128] / B-EP4D(LN) / YTLLNP2G.PRI  
[LLA129] / B-FP3D(LN) / YTLLNP0G.PRI

Following are device types supporting CP850 character set.

[LEU101] / B-EX4T1-G(EU) / YTLXUX0G.PRI  
[LEU102] / B-EX4T2-G(EU) / YTLXUX0G.PRI  
[LEU103] / B-EX4D2-G(EU) / YTLXUX0G.PRI  
[LEU104] / B-EX4T1-T(EU) / YTLXUX0T.PRI  
[LEU105] / B-EX4T2-T(EU) / YTLXUX1T.PRI  
[LEU106] / B-EX4T2-H(EU) / YTLXUX1H.PRI  
[LEU107] / B-EX4T3-H(EU) / YTLXUX3H.PRI  
[LEU108] / B-EX6T1-G(EU) / YTLXUX4G.PRI  
[LEU109] / B-EX6T3-G(EU) / YTLXUX4G.PRI  
[LEU110] / B-EX6T1-T(EU) / YTLXUX4T.PRI  
[LEU111] / B-EX6T3-T(EU) / YTLXUX4T.PRI  
[LEU112] / B-SX4T(EU) / YTLXUH0G.PRI  
[LEU113] / B-SX5T(EU) / YTLXUH1T.PRI  
[LEU114] / B-SX8T(EU) / YTLXUH2T.PRI  
[LEU115] / B-SA4TP-G(EU) / YTLXUA0G.PRI  
[LEU116] / B-SA4TM-G(EU) / YTLXUA0G.PRI  
[LEU117] / B-SA4TP-T(EU) / YTLXUA0T.PRI  
[LEU118] / B-SA4TM-T(EU) / YTLXUA0T.PRI  
[LEU119] / B-FV4D-G(EU) / YTLXUV0G.PRI  
[LEU120] / B-FV4T-G(EU) / YTLXUV0G.PRI  
[LEU121] / B-EV4D-G(EU) / YTLXUV0G.PRI  
[LEU122] / B-EV4T-G(EU) / YTLXUV0G.PRI  
[LEU123] / B-FV4D-T(EU) / YTLXUV0T.PRI  
[LEU124] / B-FV4T-T(EU) / YTLXUV0T.PRI  
[LEU125] / B-EV4D-T(EU) / YTLXUV0T.PRI  
[LEU126] / B-EV4T-T(EU) / YTLXUV0T.PRI  
[LEU127] / B-EP2D(EU) / YTLXUP1G.PRI  
[LEU128] / B-EP4D(EU) / YTLXUP2G.PRI  
[LEU129] / B-FP3D(EU) / YTLXUP0G.PRI

Following are device types supporting Japanese(Shift JIS)character set.

[LJA101] / B-EX4T1-G(JA) / YTLJAX0G.PRI  
[LJA102] / B-EX4T2-G(JA) / YTLJAX0G.PRI  
[LJA103] / B-EX4D2-G(JA) / YTLJAX0G.PRI  
[LJA104] / B-EX4T1-T(JA) / YTLJAX0T.PRI  
[LJA105] / B-EX4T2-T(JA) / YTLJAX1T.PRI  
[LJA106] / B-EX4T2-H(JA) / YTLJAX1H.PRI  
[LJA107] / B-EX4T3-H(JA) / YTLJAX3H.PRI  
[LJA108] / B-EX6T1-G(JA) / YTLJAX4G.PRI  
[LJA109] / B-EX6T3-G(JA) / YTLJAX4G.PRI  
[LJA110] / B-EX6T1-T(JA) / YTLJAX4T.PRI  
[LJA111] / B-EX6T3-T(JA) / YTLJAX4T.PRI  
[LJA112] / B-SX4T(JA) / YTLJAH0G.PRI  
[LJA113] / B-SX5T(JA) / YTLJAH1T.PRI  
[LJA114] / B-SX8T(JA) / YTLJAH2T.PRI  
[LJA115] / B-SA4TP-G(JA) / YTLJAA0G.PRI  
[LJA116] / B-SA4TM-G(JA) / YTLJAA0G.PRI  
[LJA117] / B-SA4TP-T(JA) / YTLJAA0T.PRI  
[LJA118] / B-SA4TM-T(JA) / YTLJAA0T.PRI

[LJA119] / B-FV4D-G(JA) / YTLJAV0G.PRI  
[LJA120] / B-FV4T-G(JA) / YTLJAV0G.PRI  
[LJA121] / B-EV4D-G(JA) / YTLJAV0G.PRI  
[LJA122] / B-EV4T-G(JA) / YTLJAV0G.PRI  
[LJA123] / B-FV4D-T(JA) / YTLJAV0T.PRI  
[LJA124] / B-FV4T-T(JA) / YTLJAV0T.PRI  
[LJA125] / B-EV4D-T(JA) / YTLJAV0T.PRI  
[LJA126] / B-EV4T-T(JA) / YTLJAV0T.PRI  
[LJA127] / B-EP2D(JA) / YTLJAP1G.PRI  
[LJA128] / B-EP4D(JA) / YTLJAP2G.PRI  
[LJA129] / B-FP3D(JA) / YTLJAP0G.PRI

Following are device types supporting Simplified Chinese(GB2312-EUC, MS CP936)character set.

[LSH101] / B-EX4T1-G(SH) / YTLSHX0G.PRI  
[LSH102] / B-EX4T2-G(SH) / YTLSHX0G.PRI  
[LSH103] / B-EX4D2-G(SH) / YTLSHX0G.PRI  
[LSH104] / B-EX4T1-T(SH) / YTLSHX0T.PRI  
[LSH105] / B-EX4T2-T(SH) / YTLSHX1T.PRI  
[LSH106] / B-EX4T2-H(SH) / YTLSHX1H.PRI  
[LSH107] / B-EX4T3-H(SH) / YTLSHX3H.PRI  
[LSH108] / B-EX6T1-G(SH) / YTLSHX4G.PRI  
[LSH109] / B-EX6T3-G(SH) / YTLSHX4G.PRI  
[LSH110] / B-EX6T1-T(SH) / YTLSHX4T.PRI  
[LSH111] / B-EX6T3-T(SH) / YTLSHX4T.PRI  
[LSH112] / B-SX4T(SH) / YTLSHH0G.PRI  
[LSH113] / B-SX5T(SH) / YTLSHH1T.PRI  
[LSH114] / B-SX8T(SH) / YTLSHH2T.PRI  
[LSH115] / B-SA4TP-G(SH) / YTLSHA0G.PRI  
[LSH116] / B-SA4TM-G(SH) / YTLSHA0G.PRI  
[LSH117] / B-SA4TP-T(SH) / YTLSHA0T.PRI  
[LSH118] / B-SA4TM-T(SH) / YTLSHA0T.PRI  
[LSH119] / B-FV4D-G(SH) / YTLSHV0G.PRI  
[LSH120] / B-FV4T-G(SH) / YTLSHV0G.PRI  
[LSH121] / B-EV4D-G(SH) / YTLSHV0G.PRI  
[LSH122] / B-EV4T-G(SH) / YTLSHV0G.PRI  
[LSH123] / B-FV4D-T(SH) / YTLSHV0T.PRI  
[LSH124] / B-FV4T-T(SH) / YTLSHV0T.PRI  
[LSH125] / B-EV4D-T(SH) / YTLSHV0T.PRI  
[LSH126] / B-EV4T-T(SH) / YTLSHV0T.PRI  
[LSH127] / B-EP2D(SH) / YTLSHP1G.PRI  
[LSH128] / B-EP4D(SH) / YTLSHP2G.PRI  
[LSH129] / B-FP3D(SH) / YTLSHP0G.PRI

Note:

- 1) When printing a Smart Form, user is advised to examine the actual printout of the form from the printer, rather than just relying on the print preview image.
- 2) 2D barcodes and Code128 Manual are not supported.
- 3) Outline font are not supported.
- 4) Only Monochrome bitmaps are supported and images cannot be rotated while printing.
- 5) Image compression is not supported.
- 6) Following cases may occur while printing Smart Forms:
  - a) The printer Fonts sizes may not match with the font sizes in Smartform.
  - b) Printing different smartstyles font information in same text line will result in printing the complete line in first smartstyle font.
  - c) If an object is placed outside the print area or the print start position of an object is placed within the print area but the end position is outside the print area, the part beyond the print area will be printed starting on the left end of the new line.

Details:

<Supported features>

[001] e-STUDIO5520C/6520C/6530C

TT6CI11.PRI

[PDL]: PCL

[Scripts/Languages]: ISO1 (Latin 1)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF

Output tray: Tray 1, \*Tray 2, Upper exit tray, Side exit tray

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-9999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: \*Normal, Photo, Presentation, Lineart

Halftone: \*Auto, Smooth, Detail

Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Pure black: Yes

Pure gray: Yes

Black overprint: Yes

[002] e-STUDIO2020C/2330C/2820C/2830C/3520C/3530C/4520C/3520Ci

TT4EI11.PRI

[PDL]: PCL

[Scripts/Languages]: ISO1 (Latin 1)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: Tray 1, \*Tray 2, Inner Tray  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[003] e-STUDIO205L/255/305/355/455/305S/355S/455S/305SD/355SD/455SD TT4PI11.PRI

[PDL]: PCL

[Scripts/Languages]: ISO1 (Latin 1)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, \*Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center



Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes

[004] e-STUDIO555/655/755/855

TT8NI11.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF

Output tray: Tray 1, \*Tray 2, Exit tray

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center  
Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-9999

Booklet: Yes

Font pitch: Yes

[005] e-STUDIO5520C/6520C/6530C

TT6CI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF

Output tray: Tray 1, \*Tray 2, Upper exit tray, Side exit tray

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180

degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center  
Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-9999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[006] e-STUDIO2020C/2330C/2820C/2830C/3520C/3530C/4520C/3520Ci TT4EI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: Tray 1, \*Tray 2, Inner Tray  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center  
Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail

Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[007] e-STUDIO205L/255/305/355/455/305S/355S/455S/305SD/355SD/455SD TT4PI21.PRI

[PDL]: PCL

[Scripts/Languages]: ISO2 (Latin 2)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, \*Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

[008] e-STUDIO555/655/755/855

TT8NI21.PRI

[PDL]: PCL

[Scripts/Languages]: ISO2 (Latin 2)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF  
Output tray: Tray 1, \*Tray 2, Exit tray  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-9999  
Booklet: Yes  
Font pitch: Yes

[009] e-STUDIO262CP/263CS TTC2I11.PRI

[Supported languages]: ISO1 (Latin 1)

[PDL]: PCL

[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL

[Printer Type]: Color LED Printer

[POSS (Additional print options)]

Input trays:

Double-sided Printing:

Print in color:

Password protection:

[Printer-resident bar code]:

-ARTNR, AUFNR, BARCLVS, BC\_C128B, BC\_CD39, BC\_CD39C, BC\_EAN8, BC\_EAN13, BC\_EANH, BC\_I25, BC\_I25C, BC\_PSN5, BC\_PSN9, BC\_PSN11, C128A\_00, C128A\_01, C128B\_00, C128B\_01, CD39C\_00, CD39C\_01, CD39\_\_00, CD39\_\_01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.

-BC\_93, BC\_MSI, BC\_MSIC, MC\_MSIC1 and MC\_MSIC2 are NOT supported

[SNMP Job status feedback]:

- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[010] e-STUDIO382P/332P TTM3I11.PRI

[Supported languages]: ISO1(Latin 1)

[PDL]: PCL

[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL

[Printer Type]: Monochrome LED Printer

[POSS (Additional print options)]

Input trays:

Double-sided Printing:

[Printer-resident bar code]:

-ARTNR, AUFNR, BARCLVS, BC\_C128B, BC\_CD39, BC\_CD39C, BC\_EAN8, BC\_EAN13, BC\_EANH, BC\_I25, BC\_I25C, BC\_PSN5, BC\_PSN9, BC\_PSN11, C128A\_00, C128A\_01, C128B\_00, C128B\_01, CD39C\_00, CD39C\_01, CD39\_\_00, CD39\_\_01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.

-BC\_93, BC\_MSI, BC\_MSIC, MC\_MSIC1 and MC\_MSIC2 are NOT supported

[SNMP Job status feedback]:

- All models with network connection are supported. Status feedback is limited to Pending,

Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[011] e-STUDIO223CS/222CS/222CP

TTD2I11.PRI

[Supported languages]: ISO1(Latin 1)

[PDL]: PCL

[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL

[Printer Type]: Color LED Printer

[POSS (Additional print options)]

Input trays:

Double-sided Printing:

Print in color:

[Printer-resident bar code]:

-ARTNR, AUFNR, BARCLVS, BC\_C128B, BC\_CD39, BC\_CD39C, BC\_EAN8, BC\_EAN13, BC\_EANH, BC\_I25, BC\_I25C, BC\_PSN5, BC\_PSN9, BC\_PSN11, C128A\_00, C128A\_01, C128B\_00, C128B\_01, CD39C\_00, CD39C\_01, CD39\_\_00, CD39\_\_01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.

-BC\_93, BC\_MSI, BC\_MSIC, MC\_MSIC1 and MC\_MSIC2 are NOT supported

[SNMP Job status feedback]:

- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[012] e-STUDIO5540C/6540C/6550C/5560C/6560C/6570C

TT6DI11.PRI

[PDL]: PCL

[Scripts/Languages]: ISO1 (Latin 1)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF

Output tray: Tray 1, \*Tray 2, Upper exit tray, Side exit tray

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-9999

Booklet: Yes

Font pitch: Yes

Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: \*Normal, Photo, Presentation, Lineart

Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[013] e-STUDIO2040C/2540C/3040C/3540C/4540C TT4FI11.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: Tray 1, \*Tray 2, Inner Tray  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes

Pure gray: Yes  
Black overprint: Yes

[014] e-STUDIO5540C/6540C/6550C/5560C/6560C/6570C TT6DI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF  
Output tray: Tray 1, \*Tray 2, Upper exit tray, Side exit tray  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-9999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[015] e-STUDIO2040C/2540C/3040C/3540C/4540C TT4FI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: Tray 1, \*Tray 2, Inner Tray  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[016] e-STUDIO263CS TTD2JA1.PRI

[Supported languages]: Japanese (SJIS)  
[PDL]: PCL  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI  
[Printer Type]: Color LED Printer  
[POSS (Additional print options)]  
Input trays:  
Double-sided Printing:  
Print in color:  
Password protection:  
[Printer-resident bar code]:  
-ARTNR, AUFNR, BARCLVS, BC\_C128B, BC\_CD39, BC\_CD39C, BC\_EAN8, BC\_EAN13, BC\_EANH, BC\_I25, BC\_I25C, BC\_PSN5, BC\_PSN9, BC\_PSN11, C128A\_00, C128A\_01, C128B\_00, C128B\_01, CD39C\_00, CD39C\_01, CD39\_\_00, CD39\_\_01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.  
-BC\_93, BC\_MSI, BC\_MSIC, MC\_MSIC1 and MC\_MSIC2 are NOT supported  
[SNMP Job status feedback]:  
- All models with network connection are supported. Status feedback is limited to Pending,



Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[017] e-STUDIO206L/256/306/356/456/207L/257/307/357/457/507 TT4QI11.PRI

[PDL]: PCL

[Scripts/Languages]: ISO1 (Latin 1)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, \*Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

[018] e-STUDIO556/656/756/856/557/657/757/857 TT8OI11.PRI

[PDL]: PCL

[Scripts/Languages]: ISO1 (Latin 1)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF

Output tray: Tray 1, \*Tray 2, Exit tray

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)  
Number of copies: 1-9999  
Booklet: Yes  
Font pitch: Yes

[019] e-STUDIO206L/256/306/356/456/207L/257/307/357/457/507 TT4QI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, \*Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

[020] e-STUDIO556/656/756/856/557/657/757/857 TT8O21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF

Output tray: Tray 1, \*Tray 2, Exit tray

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center

Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-9999  
Booklet: Yes  
Font pitch: Yes

[021] e-STUDIO332S TTN3I11.PRI  
[Supported languages]: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)  
[PDL]: PCL  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Monochrome LED Printer  
[POSS (Additional print options)]  
Input trays:  
Double-sided Printing:  
[Printer-resident bar code]:  
-ARTNR, AUFNR, BARCLVS, BC\_C128B, BC\_CD39, BC\_CD39C, BC\_EAN8, BC\_EAN13, BC\_EANH, BC\_I25, BC\_I25C, BC\_PSN5, BC\_PSN9, BC\_PSN11, C128A\_00, C128A\_01, C128B\_00, C128B\_01, CD39C\_00, CD39C\_01, CD39\_\_00, CD39\_\_01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.  
-BC\_93, BC\_MSI, BC\_MSIC, MC\_MSIC1 and MC\_MSIC2 are NOT supported  
[SNMP Job status feedback]:  
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[022] e-STUDIO403S TTM4I11.PRI  
[Supported languages]: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)  
[PDL]: PCL  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Monochrome LED Printer  
[POSS (Additional print options)]  
Input trays:  
Double-sided Printing:  
Password protection:  
[Printer-resident bar code]:  
-ARTNR, AUFNR, BARCLVS, BC\_C128B, BC\_CD39, BC\_CD39C, BC\_EAN8, BC\_EAN13, BC\_EANH, BC\_I25, BC\_I25C, BC\_PSN5, BC\_PSN9, BC\_PSN11, C128A\_00, C128A\_01, C128B\_00, C128B\_01, CD39C\_00, CD39C\_01, CD39\_\_00, CD39\_\_01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.  
-BC\_93, BC\_MSI, BC\_MSIC, MC\_MSIC1 and MC\_MSIC2 are NOT supported  
[SNMP Job status feedback]:  
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[023] e-STUDIO2050C/2550C/2555C/3055C/3555C/4555C/5055C TT2CI11.PRI  
[PDL]: PCL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No

[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: Tray 1, \*Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[024] e-STUDIO2050C/2550C/2555C/3055C/3555C/4555C/5055C TT2CI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, \*Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[025] e-STUDIO224CS TTE2U81.PRI  
[Supported languages]: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)  
[PDL]: PCL  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Color LED Printer  
[POSS (Additional print options)]  
Input trays:  
Double-sided Printing:  
Print in color:  
[Printer-resident bar code]:  
-ARTNR, AUFNR, BARCLVS, BC\_C128B, BC\_CD39, BC\_CD39C, BC\_EAN8, BC\_EAN13, BC\_EANH, BC\_I25, BC\_I25C, BC\_PSN5, BC\_PSN9, BC\_PSN11, C128A\_00, C128A\_01, C128B\_00, C128B\_01, CD39C\_00, CD39C\_01, CD39\_\_00, CD39\_\_01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.  
-BC\_93, BC\_MSI, BC\_MSIC, MC\_MSIC1 and MC\_MSIC2 are NOT supported  
[SNMP Job status feedback]:  
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[026] e-STUDIO263CP/264CS TTF2U81.PRI  
[Supported languages]: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)  
[PDL]: PCL  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Color LED Printer  
[POSS (Additional print options)]

Input trays:

Double-sided Printing:

Print in color:

Password protection:

[Printer-resident bar code]:

-ARTNR, AUFNR, BARCLVS, BC\_C128B, BC\_CD39, BC\_CD39C, BC\_EAN8, BC\_EAN13, BC\_EANH, BC\_I25, BC\_I25C, BC\_PSN5, BC\_PSN9, BC\_PSN11, C128A\_00, C128A\_01, C128B\_00, C128B\_01, CD39C\_00, CD39C\_01, CD39\_\_00, CD39\_\_01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.

-BC\_93, BC\_MSI, BC\_MSIC, MC\_MSIC1 and MC\_MSIC2 are NOT supported

[SNMP Job status feedback]:

- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[027] e-STUDIO383P

TTO3U81.PRI

[Supported languages]: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)

[PDL]: PCL

[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL

[Printer Type]: Monochrome LED Printer

[POSS (Additional print options)]

Input trays:

Double-sided Printing:

[Printer-resident bar code]:

-ARTNR, AUFNR, BARCLVS, BC\_C128B, BC\_CD39, BC\_CD39C, BC\_EAN8, BC\_EAN13, BC\_EANH, BC\_I25, BC\_I25C, BC\_PSN5, BC\_PSN9, BC\_PSN11, C128A\_00, C128A\_01, C128B\_00, C128B\_01, CD39C\_00, CD39C\_01, CD39\_\_00, CD39\_\_01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.

-BC\_93, BC\_MSI, BC\_MSIC, MC\_MSIC1 and MC\_MSIC2 are NOT supported

[SNMP Job status feedback]:

- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[028] Loops-LP30/e-STUDIO306LP

TT3MI11.PRI

[PDL]: PCL

[Scripts/Languages]: ISO1 (Latin 1)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: No

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, Drawer 3, Drawer 4

Output tray: \*Inner Tray, Job Separator Upper, Job Separator Lower

User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Distinguish Thin Line: Yes

[029] Loops-LP30/e-STUDIO306LP TT3MI21.PRI  
[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: No  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, Drawer 3, Drawer 4  
Output tray: \*Inner Tray, Job Separator Upper, Job Separator Lower  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Distinguish Thin Line: Yes

[030] e-STUDIO287CS/347CS/407CS TT4GI11.PRI  
[PDL]: PCL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: \*Tray 1, Inner Tray  
Stapling: \*None, Top Left, Top Right  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999

Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[031] e-STUDIO287CS/347CS/407CS TT4GI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: \*Tray 1, Inner Tray  
Stapling: \*None, Top Left, Top Right  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04



Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[032] e-STUDIO527S/477S

TT5MI11.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL  
[Color]: No  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: \*Tray 1, Inner Tray  
Stapling: \*None, Top Left, Top Right  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes

[033] e-STUDIO527S/477S

TT5MI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL  
[Color]: No  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: \*Tray 1, Inner Tray  
Stapling: \*None, Top Left, Top Right  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes

[034] Loops-LP301/e-STUDIO307LP TT3MI11.PRI  
[PDL]: PCL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: No  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, Drawer 3, Drawer 4  
Output tray: \*Inner Tray, Job Separator Upper, Job Separator Lower  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Distinguish Thin Line: Yes

[035] Loops-LP301/e-STUDIO307LP TT3MI21.PRI  
[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: No  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, Drawer 3, Drawer 4  
Output tray: \*Inner Tray, Job Separator Upper, Job Separator Lower  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Distinguish Thin Line: Yes

[036] e-STUDIO385S TTP3I11.PRI  
[PDL]: PCL5

[Scripts/Languages]: ISO1 (Latin 1)  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Monochrome laser printer  
[POSS (Additional print options)]  
Input trays selection:  
Output tray selection:  
Double-sided Printing:  
User password:  
Vendor-defined (2-up printing):

[037] e-studio385P TTQ3I11.PRI

[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Monochrome laser printer  
[POSS (Additional print options)]  
Input trays selection:  
Output tray selection:  
Double-sided Printing:  
Vendor-defined (2-up printing):

[038] e-STUDIO305CS TTC3I11.PRI

[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Color laser printer  
[POSS (Additional print options)]  
Input tray selection:  
Output tray selection:  
Print in Color/Mono:  
Double-sided Printing:  
User password:  
Vendor-defined (2-up printing):

[039] e-STUDIO305CP TTD3I11.PRI

[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Color laser printer  
[POSS (Additional print options)]  
Input tray selection:  
Output tray selection:  
Print in Color/Mono:  
Double-sided Printing:  
User password:  
Vendor-defined (2-up printing):

[040] e-STUDIO525P TTM5I11.PRI

[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL

[Printer Type]: Monochrome laser printer  
[POSS (Additional print options)]  
Input trays selection:  
Output trays selection:  
Double-sided Printing:  
Staple option:  
Hole punch option:  
User password:  
Vendor-defined (2-up printing):

[041] e-STUDIO306CS TTE3I11.PRI  
[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Monochrome laser printer  
[POSS (Additional print options)]  
Input trays selection:  
Output trays selection:  
Double-sided Printing:  
Staple option:  
Hole punch option:  
User password:  
Vendor-defined (2-up printing):

[042] e-STUDIO425S TTN4I11.PRI  
[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Monochrome laser printer  
[POSS (Additional print options)]  
Input trays selection:  
Output trays selection:  
Double-sided Printing:  
Staple option:  
Hole punch option:  
User password:  
Vendor-defined (2-up printing):

[043] e-STUDIO2000AC/2500AC/2005AC/2505AC/3005AC/3505AC/4505AC/5005AC  
TT5CI11.PRI  
[PDL]: PCL  
[Scripts/Languages]: ISO1+UPE (Latin 1+Unicode Print Enable)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold, Anywhere

Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: Tray 1, \*Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Project Code: Yes (63 characters)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[044] e-STUDIO2000AC/2500AC/2005AC/2505AC/3005AC/3505AC/4505AC/5005AC  
TT5CI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold, Anywhere  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: Tray 1, \*Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes

Department code: Yes (5 digit numbers)  
Project Code: Yes (63 characters)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[045] e-STUDIO2008A/2508A/3008A/3508A/4508A/5008A TT5NI11.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO1+UPE (Latin 1+Unicode Print Enable)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold, Anywhere  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: Tray 1, \*Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Project Code: Yes (63 characters)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes

[046] e-STUDIO2008A/2508A/3008A/3508A/4508A/5008A TT5NI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)

[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold, Anywhere  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4  
Output tray: Tray 1, \*Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Project Code: Yes (63 characters)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes

[047] e-STUDIO5506AC/6506AC/7506AC

TT7CI11.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO1+UPE (Latin 1+Unicode Print Enable)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold, Anywhere  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF  
Output tray: Tray 1, \*Tray 2, Upper exit tray, Side exit tray  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Project Code: Yes (63 characters)  
Number of copies: 1-9999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW

Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[048] e-STUDIO5506AC/6506AC/7506AC

TT7CI21.PRI

[PDL]: PCL  
[Scripts/Languages]: ISO2 (Latin 2)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident bar code]: No  
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL  
[Color]: Yes  
[Input trays]: Yes (See [POSS] section for details.)  
[SNMP Job status feedback]: No  
[POSS (Print Options for SAPScripts and Smartforms)]  
\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold, Anywhere  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF  
Output tray: Tray 1, \*Tray 2, Upper exit tray, Side exit tray  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Project Code: Yes (63 characters)  
Number of copies: 1-9999  
Booklet: Yes  
Font pitch: Yes  
Color: Color, Grayscale, \*Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW  
Image quality type: \*Normal, Photo, Presentation, Lineart  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Cyan: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Magenta: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Yellow: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Saturation: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Background adjustment: FC, FD, FE, FF, \*00, 01, 02, 03, 04



Pure black: Yes  
Pure gray: Yes  
Black overprint: Yes

[049] e-STUDIO5508A/6508A/7508A/8508A

TT8PI11.PRI

[PDL]: PCL

[Scripts/Languages]: ISO1+UPE (Latin 1+Unicode Print Enable)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold, Anywhere

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF

Output tray: Tray 1, \*Tray 2, Exit tray

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Project Code: Yes (63 characters)

Number of copies: 1-9999

Booklet: Yes

Font pitch: Yes

[050] e-STUDIO5508A/6508A/7508A/8508A

TT8PI21.PRI

[PDL]: PCL

[Scripts/Languages]: ISO2 (Latin 2)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold, Anywhere

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF

Output tray: Tray 1, \*Tray 2, Exit tray

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center

Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Project Code: Yes (63 characters)  
Number of copies: 1-9999  
Booklet: Yes  
Font pitch: Yes

[051] e-STUDIO3508LP\_Loops-LP35/4508LP\_Loops-LP45/5008LP\_Loops-LP50 TT5OI11.PRI

[PDL]: PCL

[Scripts/Languages]: ISO1+UPE (Latin 1+Unicode Print Enable)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: No

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file

Print Mode: \*Normal, Proof, Private, Hold, Anywhere

Collate: \*Sort, Group, Rotated Sort

Duplex: \*None, Long Edge, Short Edge

Orientation: \*Portrait, Landscape

Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, Drawer 3, Drawer 4

Output tray: \*Inner Tray, Job Separator Upper, Job Separator Lower

Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation

Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double

User login: Yes

Department code: Yes (5 digit numbers)

Number of copies: 1-999

Booklet: Yes

Font pitch: Yes

Halftone: \*Auto, Smooth, Detail

Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04

Distinguish Thin Line: Yes

Project Code: Yes (63 characters)

Erasable Toner: erasable blue

[052] e-STUDIO3508LP\_Loops-LP35/4508LP\_Loops-LP45/5008LP\_Loops-LP50 TT5OI21.PRI

[PDL]: PCL

[Scripts/Languages]: ISO2 (Latin 2)

[Graphics]: Yes

[OCR]: No

[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: No

[Input trays]: Yes (See [POSS] section for details.)

[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]

\* denotes the default value in the device type file  
Print Mode: \*Normal, Proof, Private, Hold, Anywhere  
Collate: \*Sort, Group, Rotated Sort  
Duplex: \*None, Long Edge, Short Edge  
Orientation: \*Portrait, Landscape  
Input Tray: \*Auto, Bypass Tray, Drawer 1, Drawer 2, Drawer 3, Drawer 4  
Output tray: \*Inner Tray, Job Separator Upper, Job Separator Lower  
Halftone: \*Auto, Smooth, Detail  
Hole punch: \*None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation  
Stapling: \*None, Top Left, Left, Bottom Left, Top Right, Right, Bottom Right, Top, Bottom, Center Double  
User login: Yes  
Department code: Yes (5 digit numbers)  
Number of copies: 1-999  
Booklet: Yes  
Font pitch: Yes  
Halftone: \*Auto, Smooth, Detail  
Color Balance - Black: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Sharpness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Brightness: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Contrast: FC, FD, FE, FF, \*00, 01, 02, 03, 04  
Distinguish Thin Line: Yes  
Project Code: Yes (63 characters)  
Erasable Toner: erasable blue

[053] e-STUDIO408S TTO4I11.PRI  
[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Monochrome laser printer  
[POSS (Additional print options)]  
Input trays selection:  
Output trays selection:  
Double-sided Printing:  
Staple option:  
Hole punch option:  
User password:  
Vendor-defined (2-up printing):

[054] e-STUDIO448S TTP4I11.PRI  
[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Monochrome laser printer  
[POSS (Additional print options)]  
Input trays selection:  
Output trays selection:  
Double-sided Printing:  
Staple option:  
Hole punch option:  
User password:  
Vendor-defined (2-up printing):

[055] e-STUDIO478S TTQ4I11.PRI  
[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL

[Printer Type]: Monochrome laser printer  
[POSS (Additional print options)]  
Input trays selection:  
Output trays selection:  
Double-sided Printing:  
Staple option:  
Hole punch option:  
User password:  
Vendor-defined (2-up printing):

[056] e-STUDIO408P TTR4I11.PRI  
[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Color laser printer  
[POSS (Additional print options)]  
Input tray selection:  
Output tray selection:  
Print in Color/Mono:  
Double-sided Printing:  
User password:  
Vendor-defined (2-up printing):

[057] e-STUDIO478P TTS4I11.PRI  
[Scripts/Languages]: ISO1 (Latin 1)  
[PDL]: PCL5  
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL  
[Printer Type]: Color laser printer  
[POSS (Additional print options)]  
Input tray selection:  
Output tray selection:  
Print in Color/Mono:  
Double-sided Printing:  
User password:  
Vendor-defined (2-up printing):

#### Details (Label Printers):

<Supported features>  
[L001] B-EX 203dpi TTLZBI12.PRI  
[PDL]: ZPLII  
[Printer driver]: LZPL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Paper sizes]: No  
[Color]: No  
[Input trays]: No  
[SNMP Job status feedback]: No

[L002] B-EX 300dpi TTLZBI13.PRI  
[PDL]: ZPLII  
[Printer driver]: LZPL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes

[OCR]: No  
[Printer-resident barcode]: Yes  
[Paper sizes]: No  
[Color]: No  
[Input trays]: No  
[SNMP Job status feedback]: No

[L003] B-EX 600dpi TTLZBI16.PRI  
[PDL]: ZPLII  
[Printer driver]: LZPL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Paper sizes]: No  
[Color]: No  
[Input trays]: No  
[SNMP Job status feedback]: No

[L004] B-SA 203dpi TTLZBI12.PRI  
[PDL]: ZPLII  
[Printer driver]: LZPL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Paper sizes]: No  
[Color]: No  
[Input trays]: No  
[SNMP Job status feedback]: No

[L005] B-SA 300dpi TTLZBI13.PRI  
[PDL]: ZPLII  
[Printer driver]: LZPL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Paper sizes]: No  
[Color]: No  
[Input trays]: No  
[SNMP Job status feedback]: No

[L006] B-SX6T TTLZBI13.PRI  
[PDL]: ZPLII  
[Printer driver]: LZPL  
[Scripts/Languages]: ISO1 (Latin 1)  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Paper sizes]: No  
[Color]: No  
[Input trays]: No  
[SNMP Job status feedback]: No

[LLA101] B-EX4T1-G(LN)  
[Device type Name]: YTLLNX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA102] B-EX4T2-G(LN)  
[Device type Name]: YTLLNX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA103] B-EX4D2-G(LN)  
[Device type Name]: YTLLNX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA104] B-EX4T1-T(LN)  
[Device type Name]: YTLLNX0T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA105] B-EX4T2-T(LN)  
[Device type Name]: YTLLNX1T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA106] B-EX4T2-H(LN)  
[Device type Name]: YTLLNX1H.PRI  
[DPI]: 600  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes

[Color]: No  
[SNMP Job status feedback]: No

[LLA107] B-EX4T3-H(LN)  
[Device type Name]: YTLLNX3H.PRI  
[DPI]: 600  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA108] B-EX6T1-G(LN)  
[Device type Name]: YTLLNX4G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA109] B-EX6T3-G(LN)  
[Device type Name]: YTLLNX4G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA110] B-EX6T1-T(LN)  
[Device type Name]: YTLLNX4T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA111] B-EX6T3-T(LN)  
[Device type Name]: YTLLNX4T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA112] B-SX4T(LN)  
[Device type Name]: YTLLNH0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes

[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA113] B-SX5T(LN)  
[Device type Name]: YTLLNH1T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA114] B-SX8T(LN)  
[Device type Name]: YTLLNH2T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA115] B-SA4TP-G(LN)  
[Device type Name]: YTLLNA0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA116] B-SA4TM-G(LN)  
[Device type Name]: YTLLNA0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA117] B-SA4TP-T(LN)  
[Device type Name]: YTLLNA0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA118] B-SA4TM-T(LN)  
[Device type Name]: YTLLNA0T.PRI  
[DPI]: 300



[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA119] B-FV4D-G(LN)  
[Device type Name]: YTLLNV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA120] B-FV4T-G(LN)  
[Device type Name]: YTLLNV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA121] B-EV4D-G(LN)  
[Device type Name]: YTLLNV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA122] B-EV4T-G(LN)  
[Device type Name]: YTLLNV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA123] B-FV4D-T(LN)  
[Device type Name]: YTLLNV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA124] B-FV4T-T(LN)  
[Device type Name]: YTLLNV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA125] B-EV4D-T(LN)  
[Device type Name]: YTLLNV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA126] B-EV4T-T(LN)  
[Device type Name]: YTLLNV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA127] B-EP2D(LN)  
[Device type Name]: YTLLNP1G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA128] B-EP4D(LN)  
[Device type Name]: YTLLNP2G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LLA129] B-FP3D(LN)  
[Device type Name]: YTLLNP0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes

[Color]: No  
[SNMP Job status feedback]: No

[LEU101] B-EX4T1-G(EU)  
[Device type Name]: YTLEUX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU102] B-EX4T2-G(EU)  
[Device type Name]: YTLEUX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU103] B-EX4D2-G(EU)  
[Device type Name]: YTLEUX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU104] B-EX4T1-T(EU)  
[Device type Name]: YTLEUX0T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU105] B-EX4T2-T(EU)  
[Device type Name]: YTLEUX1T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU106] B-EX4T2-H(EU)  
[Device type Name]: YTLEUX1H.PRI  
[DPI]: 600  
[PDL]: TPCL

[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU107] B-EX4T3-H(EU)  
[Device type Name]: YTLEUX3H.PRI  
[DPI]: 600  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU108] B-EX6T1-G(EU)  
[Device type Name]: YTLEUX4G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU109] B-EX6T3-G(EU)  
[Device type Name]: YTLEUX4G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU110] B-EX6T1-T(EU)  
[Device type Name]: YTLEUX4T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU111] B-EX6T3-T(EU)  
[Device type Name]: YTLEUX4T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU112] B-SX4T(EU)  
[Device type Name]: YTLEUH0G.PRI

[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU113] B-SX5T(EU)  
[Device type Name]: YTLEUH1T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU114] B-SX8T(EU)  
[Device type Name]: YTLEUH2T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU115] B-SA4TP-G(EU)  
[Device type Name]: YTLEUA0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU116] B-SA4TM-G(EU)  
[Device type Name]: YTLEUA0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU117] B-SA4TP-T(EU)  
[Device type Name]: YTLEUA0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU118] B-SA4TM-T(EU)  
[Device type Name]: YTLEUA0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU119] B-FV4D-G(EU)  
[Device type Name]: YTLEUV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU120] B-FV4T-G(EU)  
[Device type Name]: YTLEUV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU121] B-EV4D-G(EU)  
[Device type Name]: YTLEUV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU122] B-EV4T-G(EU)  
[Device type Name]: YTLEUV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU123] B-FV4D-T(EU)  
[Device type Name]: YTLEUV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes

[Color]: No  
[SNMP Job status feedback]: No

[LEU124] B-FV4T-T(EU)  
[Device type Name]: YTLEUV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU125] B-EV4D-T(EU)  
[Device type Name]: YTLEUV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU126] B-EV4T-T(EU)  
[Device type Name]: YTLEUV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU127] B-EP2D(EU)  
[Device type Name]: YTLEUP1G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU128] B-EP4D(EU)  
[Device type Name]: YTLEUP2G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LEU129] B-FP3D(EU)  
[Device type Name]: YTLEUP0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes

[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA101] B-EX4T1-G(JA)  
[Device type Name]: YTLJAX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA102] B-EX4T2-G(JA)  
[Device type Name]: YTLJAX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA103] B-EX4D2-G(JA)  
[Device type Name]: YTLJAX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA104] B-EX4T1-T(JA)  
[Device type Name]: YTLJAX0T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA105] B-EX4T2-T(JA)  
[Device type Name]: YTLJAX1T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA106] B-EX4T2-H(JA)  
[Device type Name]: YTLJAX1H.PRI



[DPI]: 600  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA107] B-EX4T3-H(JA)  
[Device type Name]: YTLJAX3H.PRI  
[DPI]: 600  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA108] B-EX6T1-G(JA)  
[Device type Name]: YTLJAX4G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA109] B-EX6T3-G(JA)  
[Device type Name]: YTLJAX4G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA110] B-EX6T1-T(JA)  
[Device type Name]: YTLJAX4T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA111] B-EX6T3-T(JA)  
[Device type Name]: YTLJAX4T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA112] B-SX4T(JA)  
[Device type Name]: YTLJAH0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA113] B-SX5T(JA)  
[Device type Name]: YTLJAH1T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA114] B-SX8T(JA)  
[Device type Name]: YTLJAH2T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA115] B-SA4TP-G(JA)  
[Device type Name]: YTLJAA0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA116] B-SA4TM-G(JA)  
[Device type Name]: YTLJAA0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA117] B-SA4TP-T(JA)  
[Device type Name]: YTLJAA0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes

[Color]: No  
[SNMP Job status feedback]: No

[LJA118] B-SA4TM-T(JA)  
[Device type Name]: YTLJAA0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA119] B-FV4D-G(JA)  
[Device type Name]: YTLJAV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA120] B-FV4T-G(JA)  
[Device type Name]: YTLJAV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA121] B-EV4D-G(JA)  
[Device type Name]: YTLJAV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA122] B-EV4T-G(JA)  
[Device type Name]: YTLJAV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA123] B-FV4D-T(JA)  
[Device type Name]: YTLJAV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes

[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA124] B-FV4T-T(JA)  
[Device type Name]: YTLJAV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA125] B-EV4D-T(JA)  
[Device type Name]: YTLJAV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA126] B-EV4T-T(JA)  
[Device type Name]: YTLJAV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA127] B-EP2D(JA)  
[Device type Name]: YTLJAP1G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA128] B-EP4D(JA)  
[Device type Name]: YTLJAP2G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LJA129] B-FP3D(JA)  
[Device type Name]: YTLJAP0G.PRI  
[DPI]: 203

[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH101] B-EX4T1-G(SH)  
[Device type Name]: YTLSHX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH102] B-EX4T2-G(SH)  
[Device type Name]: YTLSHX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH103] B-EX4D2-G(SH)  
[Device type Name]: YTLSHX0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH104] B-EX4T1-T(SH)  
[Device type Name]: YTLSHX0T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH105] B-EX4T2-T(SH)  
[Device type Name]: YTLSHX1T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH106] B-EX4T2-H(SH)  
[Device type Name]: YTLSHX1H.PRI  
[DPI]: 600  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH107] B-EX4T3-H(SH)  
[Device type Name]: YTLSHX3H.PRI  
[DPI]: 600  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH108] B-EX6T1-G(SH)  
[Device type Name]: YTLSHX4G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH109] B-EX6T3-G(SH)  
[Device type Name]: YTLSHX4G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH110] B-EX6T1-T(SH)  
[Device type Name]: YTLSHX4T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH111] B-EX6T3-T(SH)  
[Device type Name]: YTLSHX4T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes

[Color]: No  
[SNMP Job status feedback]: No

[LSH112] B-SX4T(SH)  
[Device type Name]: YTLSSH0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH113] B-SX5T(SH)  
[Device type Name]: YTLSSH1T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH114] B-SX8T(SH)  
[Device type Name]: YTLSSH2T.PRI  
[DPI]: 305  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH115] B-SA4TP-G(SH)  
[Device type Name]: YTLSHA0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH116] B-SA4TM-G(SH)  
[Device type Name]: YTLSHA0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH117] B-SA4TP-T(SH)  
[Device type Name]: YTLSHA0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes

[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH118] B-SA4TM-T(SH)  
[Device type Name]: YTLSHA0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH119] B-FV4D-G(SH)  
[Device type Name]: YTLSHV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH120] B-FV4T-G(SH)  
[Device type Name]: YTLSHV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH121] B-EV4D-G(SH)  
[Device type Name]: YTLSHV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH122] B-EV4T-G(SH)  
[Device type Name]: YTLSHV0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH123] B-FV4D-T(SH)  
[Device type Name]: YTLSHV0T.PRI  
[DPI]: 300



[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH124] B-FV4T-T(SH)  
[Device type Name]: YTLSHV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH125] B-EV4D-T(SH)  
[Device type Name]: YTLSHV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH126] B-EV4T-T(SH)  
[Device type Name]: YTLSHV0T.PRI  
[DPI]: 300  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH127] B-EP2D(SH)  
[Device type Name]: YTLSHP1G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH128] B-EP4D(SH)  
[Device type Name]: YTLSHP2G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

[LSH129] B-FP3D(SH)  
[Device type Name]: YTLSHP0G.PRI  
[DPI]: 203  
[PDL]: TPCL  
[Graphics]: Yes  
[OCR]: No  
[Printer-resident barcode]: Yes  
[Color]: No  
[SNMP Job status feedback]: No

#### Revision History

[05 August 2011]

- Updated device typefiles [001], [002], [003], [004], [005], [006], [007], [008] to Version 1.1.
- Fixed paper size issue in ABAP printing.

[02 April 2012]

- Added device type files [017], [018], [019], [020] (Version 1).

[20 August 2012]

- Added device type files [023], [024] (Version 1).

[18 February 2013]

- Added device type files [025], [026], [027] (Version 1).

[26 February 2013]

- Added Label Printer description and device type files [L001], [L002], [L003], [L004].

[05 March 2013]

- Changed to support LZPL driver in [L001], [L002] Label printers.

[29 March 2013]

- Added Label printer description and device type file [L003].

[17 June 2013]

- Added support for additional printer models [L004] and [L005].

[05 July 2013]

- Added new models to device type files [023] and [024]. (Version remains to be 1.)
- Added device type files [028], [029], [030], [031], [032], [033] (Version 1).

[25 July 2013]

- Added support for additional printer model [L006].

[27 February 2014]

- Added new models to device type files [012] and [014]. (Version remains to be 1.)

[04 June 2014]

- Added new models to device type files [017], [018], [019] and [020]. (Version remains to be 1.)

[26 Dec 2014]

- Added device type files [034], [035] (Version 1).

[24 Feb 2015]

- Added new models to device type files [036], [037], [038], [039] and [040]. (Version remains to be 1.)

[25 Mar 2016]

- Added new models to device type files [041] and [042]. (Version1.)

[27 Apr 2016]  
- Added new models to device type files [043],[044],[045] and [046]. (Version1.)

[12 Jul 2016]  
- Added new models to device type files [047],[048],[049] and [050]. (Version1.)

[26 Apr 2017]  
- Added new models to device type files [051] and [052]. (Version1.)  
- Changed support language for device type files [043], [045], [047] and [049].

[09 Mar 2018]  
- Added new models to device type files [053],[054],[055],[056] and [057]. (Version1.)

[29 Jun 2018]  
- Supported TPCL printing in Smartforms with different Device Types [ Lxx101] to [Lxx129], xx varies based on Device Type.

Validity

This document is not restricted to a software component or software component version

References

This document refers to:

SAP Notes  
750772 [Information about ZPL-II printer driver for Smart Forms](#)

This document is referenced by:

Customer Incident (25)

Number	Year	Title	Status	Processor	Customer Number	Customer Name
0000000000	0000					

[more...](#)  
SAP Notes (2)  
1097990 [List of Printer Vendor Wizard Notes](#)  
135894 [Label printing on thermal \(transfer\) printers](#)

Attachments

File Name	File Size (KB)	Mime Type
<a href="#">TOSHIBA_TEC_Label_DevTyps.ZIP</a>	12	application/x-zip-compressed
<a href="#">TOSHIBA_TEC_DevTyps.ZIP</a>	1988	application/x-zip-compressed
<a href="#">TOSHIBA_TEC_DevTyps_Rev_2.zip</a>	655	application/x-zip-compressed
<a href="#">TOSHIBA_TEC_Label_DevTyps_TPCL.zip</a>	654	application/x-zip-compressed